



# ADHESIVA S

## WALL COVERING

Technical Data Sheet

Revised: 04/2021

### DESCRIPTION

Powder adhesive for light and heavy paper- backed vinyl wall coverings. It can also be used in combination with all ACM Starch products.

- + Does not stain
- + Strong initial tack
- + High yield
- + Zero C.O.V.
- + Antibacterial and anti-mold properties
- + Ready for action within 5 minutes after dilution

Suitable for:

- all types of wall coverings
- paper-backed vinyl wall coverings
- expanded wall coverings
- vinyl wall coverings up to 600 gr/m<sup>2</sup>
- paper duplex

### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

### PREPARATION AND YIELD OF THE ADHESIVE

Dilute ADHESIVA S in clean water according to the table:

DILUTION PER 250 G			m <sup>2</sup>
Prepare and sealing	10 l	-	80
Wallpaper + duplex	7 l	8	50
Vinyl and expanded	6 l	7	40
Heavy vinyl	5 l	5	30

1. Vigorously mix the water.
2. Dilute the contents of the bag in cold water, stirring continuously.
3. Wait 3 minutes.
4. Mix again.
5. The product is ready for use after 5 minutes.



### APPLICATION OF THE ADHESIVE

Apply the adhesive evenly on the back of the wall covering. Fold the sheet back on itself and wait 10-20 minutes depending on the ambient temperatures. Proceed following the application of the sheet.

Video tutorial: <https://www.youtube.com/watch?v=j7zO9ekpbRg>

### CLEANING

Clean possible spills with a damp sponge. The product does not stain.

### CONTRAINDICATIONS

The product is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately.

### PACKAGES

Box of 250 g (24 pcs x 250 g)	code 10111
Box of 600 g (12 pcs x 600 g)	code 10111-600
Box of 1 Kg (12 pcs x 1Kg)	code 10111-1-12

### STORAGE

The product is guaranteed for 60 months from the date of production. Do not freeze. Store in a dry place.

### TECHNICAL DATA

base:	starch
appearance:	flakes
color:	white
percentage of solid:	100%
customs code:	3505 2030
flash:	no
application temperature:	+ 5 °C + 40 °C
waiting time:	10 - 20 minutes
open time:	20 - 30 minutes
setting time:	48 hours
not harmful	
not sensitive to frost	

### FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI  
PHONE +39 02 903 611 48 | [laboratorio@acm-italy.com](mailto:laboratorio@acm-italy.com) | [www.acm-italy.com](http://www.acm-italy.com)