



ACROSIL A

BUILDING PRODUCTS

Technical Data Sheet

Revised: 01/10/2018

DESCRIPTION

Acetic silicon to seal bathrooms, showers, sinks, etc. Suitable for wet areas. It protects the seals from mildew.

- + Excellent adhesion on all non-porous surfaces (glass, aluminum, ceramics).
- + Great to maintain a high standard of hygiene in wet areas
- + It prevents mildew in the sealed joints
- + Not paintable
- + White and transparent

Suitable for:

- sealing leaks in showers, saunas and bathrooms.
- special for marine industry to seal galleys and refrigerator rooms.
- sealing windows in high humidity areas.
- sealing metal sheet elements in kitchens.
- particularly suitable for seals in hygienic environment or health (clinics, hospitals).
- suitable in DIY market.

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils.

HOW TO USE IT

Cut the seal of the cartridge and use a special gun for cartridges.

APPLICATION

Apply the elements so that ACROSIL A touch all the points of surface .

CONSUMPTION

About 14 linear meters per cartridge.

CLEANING

It is advisable to remove with spatula when is wet and mechanically when is dry.

CONTRAINDICATIONS

- + Do not use at temperatures below + 5 °C
- + Application is recommended between 10 °C and + 40 °C

PACKAGES

Cartridge 280 ml

code 30151

STORAGE

The product is guaranteed for 24 months from the date of production.

TECHNICAL DATA

base:	acetic
appearance:	white or transparent
percentage of solid:	80%
customs code:	3506 9190
application temperature:	+10 °C + 40 °C
waiting time:	none
open time:	20 minutes
setting time:	24 hours

FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com