



ADHESIL

WALL COVERING

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Powder adhesive for wall coverings with paper and paper support.

- + Does not stain
- + Strong initial tack
- + High yield
- + Antibacterial and anti-mold properties
- + Ready for action within 5 minutes after dilution

Suitable for:

- all types of wall coverings
- vinyl wall coverings with paper backing
- paper duplex
- expanded vinyl wall coverings with paper backing up to a maximum of 250 g/m²

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

PREPARATION AND YIELD OF THE ADHESIVE

Dilute ADHESIL in clean water according to the table:

DILUTION FOR 125G			m ²
Normal wallpapers	9 l	9	60
Heavy wallpapers	8 l	8	50
Heavier wallpapers	6 l	6	30

1. Vigorously mix the water
2. Dilute the contents of the bag in cold water, stirring continuously
3. Wait 3 minutes
4. Mix again
5. The product is ready for use after 5 minutes



APPLICATION

Apply the adhesive on the back of the wall covering with a brush or brush pholsterer or short wool roll.

Brush - apply the adhesive evenly on the back of the wall covering. Fold the sheet back on itself and wait 10-20 minutes depending on the ambient temperatures. Proceed following the application of the sheet.

Video tutorial: <https://www.Youtube.Com/watch?V=j7zo9ekpbrg>

CLEANING

We recommend to clean the wall coverings from excess adhesive and the joints with a wet sponge.

Clean possible spills with a damp sponge.

We also recommend to consult the cleaning instructions of the wall covering's manufacturer before installation.

THE PRODUCT DOES NOT STAIN.

CONTRAINDICATIONS

The product is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately.

PACKAGES

box 125 gr.
(40 pcs. x 125 gr)

cod. 10017

STORAGE

The product is guaranteed for 60 months from the date of production. Do not freeze. Store in a dry place.

TECHNICAL DATA

base:
physical appearance:
color:
solid content %:
customs code:
application temperature:
waiting time:
open time:
definitive adhesion:
non flammable
not harmful
not sensitive to frost

cellulose
powder
white
100%
3505 2030
+ 5 °C - + 40 °C
10 - 20 minutes
20 - 30 minutes
48 hours

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com