



# ADHESIVA UNIFIX

## BUILDING PRODUCTS

Technical Data Sheet

Revised: 01/10/2018

### **DESCRIPTION**

Acrylic water-based mastic adhesive, ideal product for bonding structural elements in the building industry, thermo-acoustic insulation materials, etc.

Strong suction cup effect, strong initial adherence.

- + No highly flammable solvents
- + Free labelling EC
- + Low shrinkage
- + No nails required

Suitable for:

- structural bonding in construction
- wood/ PVC/ ceramic skirting boards
- application of tiles and ceramic mural
- polystyrene and polyurethane panels, frames and rosettes
- cork and thermo-acoustic materials
- applications in DIY

### **PREPARING THE SURFACE**

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy.

### **PREPARATION**

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer. Unroll or simply unpack the flooring to be laid in order to decrease tensions and folds.

### **PREPARATION OF ADHESIVE**

The adhesive is ready for use.

### **APPLICATION**

Apply ADHESIVA UNIFIX all over the contact surface

### **CONSUMPTION**

About 20 linear meters per cartridge.  
100-300 g/m<sup>2</sup> when applied by trowels

### **CLEANING**

Clean the equipment with fresh water, immediately after use.

### **CONTRAINDICATIONS**

- + Do not use at temperatures below than + 3 °C
- + Application is recommended between + 10 °C to + 35 °C

### **PACKAGES**

310 ml cartridge	code 30076
700 g jar	code 30078
Bucket 6 kg	code 30079
Bucket 13 kg	code 30080
Bucket 20 kg	code 30081

### **STORAGE**

The product is guaranteed for 24 months from the production date

### **TECHNICAL DATA**

base:	acrylic
appearance:	extra white color (or colored if requested)
percentage of solid:	80%
customs code:	3506 9190
application temperature:	+ 10°C + 35°C
waiting time:	none
open time:	30 - 40 minutes
setting time:	48/72 hours

### **FINAL PROVISIONS**

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com