



PAPEREMOVER

WALL COVERING

Technical Data Sheet

Revised: 01/10/2018

DESCRIPTION

Concentrate wallpaper remover, ideal product for non-woven wall coverings, wall paintings and washable coverings.

- + Exceptional effectiveness
- + High yield
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties

Suitable for:

- Detached wallpapers
- Detached paper backed vinyl wallpapers or non-woven wall coverings.
- Detached expanded wall coverings
- fiberglass wall coverings
- Old washable wall paintings

PRODUCT PREPARATION

Dilute 200 g of PAPEREMOVER with a maximum of 8 liters of water before the use.

As for mural paintings, it is recommended to dilute the product with 5 liters of water.

PRODUCT APPLICATION

Once diluted, spread the product on the wall covering you want to remove with a roller or a brush.

Wait about 10 minutes and then remove the cover with a metal spatula. In case of highly absorbent walls or strong adhesives, it is recommended to apply a second coat of diluted PAPEREMOVER.

CONSUMPTION

Approximately 40 m² in box.

CONTRAINdicATIONS

As for paper-backed vinyl, it is recommended to remove the part of the PVC coating or proceed with the engravings on the PVC before applying the product.

PACKAGES

Bottle of 200 g (in boxes of 25 pieces No.)

code 10012

STORAGE

The product is guaranteed for 24 months from the date of production. Not sensitive to frost. The product does not stain

TECHNICAL DATA

base:	surfactant
appearance:	liquid
pH:	4.5
viscosity:	200 cps
customs code:	3505 2030
c.o.v.	<0.05 g/m ³
percentage of solid:	about 10-15%
application temperature:	+ 5 °C + 40 °C
waiting time:	10 - 15 minutes
non flammable	

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com