



PAPEREMOVER

WALL COVERING

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Concentrate wallpaper remover, ideal product for non-woven wall coverings, wall paintings and washable coverings.

- + Exceptional effectiveness
- + High yield
- + Low V.O.C. (Volatile Organic Compounds)
- + antibacterial and anti-mold properties

Suitable for:

- Detached wallpapers
- Detached paper backed vinyl wallpapers or non-woven wall coverings.
- Detached expanded wall coverings
- fiberglass wall coverings
- Old washable wall paintings

PRODUCT PREPARATION

Dilute 200 g of PAPEREMOVER with a maximum of 8 liters of water before the use.

As for mural paintings, it is recommended to dilute the product with 5 liters of water.

PRODUCT APPLICATION

Once diluted, spread the product on the wall covering you want to remove with a roller or a brush.

Wait about 10 minutes and then remove the cover with a metal spatula. In case of highly absorbent walls or strong adhesives, it is recommended to apply a second coat of diluted PAPEREMOVER.

CONSUMPTION

Approximately 40 m² in box.

CONTRAINdicATIONS

As for paper-backed vinyl, it is recommended to remove the part of the PVC coating or proceed with the engravings on the PVC before applying the product.

PACKAGES

Bottle of 200 g (in boxes of 25 pieces No.)

code 10012-N

STORAGE

The product is guaranteed for 24 months from the date of production. Not sensitive to frost. The product does not stain

TECHNICAL DATA

base:	surfactant
appearance:	liquid
pH:	4.5
viscosity:	200 cps
customs code:	3505 2010
V.O.C.	< 0,005 mg/m ³
percentage of solid:	about 10-15%
application temperature:	+ 5 °C + 40 °C
waiting time:	10 - 15 minutes
non flammable	

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com