



# PLASTER

## BUILDING PRODUCTS

Technical Data Sheet

Revised: 04/2021

### DESCRIPTION

Acrylic waterproofing sheath suitable to the protection of baths, showers, terraces and balconies.

- + Exceptional effectiveness
- + High yield
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties
- + Walkable

Suitable for:

- Waterproofing tile fundings in bathrooms, showers and damp rooms.
- balcony and terrace Waterproofing.
- flat roof and damp floor Waterproofing.

### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

### PREPARATION

PLASTER is a ready to use product. It is recommended to dilute the first coat with 5% of water.

### PRODUCT APPLICATION

Once diluted, spread the product with a roller or a brush. Wait the product to be dried (about 8 hours) and then proceed with the second coat.

### CONSUMPTION

About 1000/1500 g/m<sup>2</sup> (in 2 coats)

### CLEANING

Clean the equipment with fresh water, immediately after use.

### CONTRAINDICATIONS

Do not apply on non-absorbent substrates.

In case of ceramic tiles we recommend to sand the surface to make it porous.

Before the laying, spread a coat of PRIMER AC. Dilute it 1: 5 with water. DO NOT FREEZE.

### PACKAGES

Jar of 750 ml (box 24 pieces)	code 30134B, 30137R/T/V
Tin 5 l (box 4 pieces)	code 30135B/G, 30138R/T/V
Tins of 8 l	code 30136B, 30139R/T/V
Tins of 14 l	code 30117B/G, 30140R/T/V

### STORAGE

The product is guaranteed for 24 months from the date of production.

### TECHNICAL DATA

base:	acrylic
appearance:	creamy paste
colors:	white, gray, green, red
pH:	6,5
viscosity:	2,500 cps
percentage of solid:	70%
customs code:	3506 9100
application temperature:	+ 5°C + 40°C
waiting time:	6/8 hours
non flammable	

### FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com