



# SEACRIL N

## BUILDING PRODUCTS

Technical Data Sheet

Revised: 01/10/2018

### **DESCRIPTION**

Paintable and extra white water-based acrylic sealant.  
Suction cup effect, strong initial tack.

- + No highly flammable solvents
- + Free labeling EC
- + Low shrinkage

Suitable for:

- sealing cracks on walls, plasterboards and tiles.
- sealing joints between plasterboard and metal supports
- polystyrene and polyurethane Panels frames and rosettes
- cork and thermo-acoustic materials
- applications in DIY
- no nails support required
- strong suction cup effect
- elastic and paintable

### **SURFACE PREPARATION**

All surfaces must be dry, absorbent, strong, free of dust or paints or oils.  
Any cracks must be sealed with our 2-component epoxy adhesive Epoxy.

### **PREPARATION**

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer.  
Unroll or simply unpack the flooring to be laid in order to decrease tensions and folds.

### **ADHESIVE PREPARATION**

The adhesive is ready for use. Cut the seal of the cartridge and use a special gun for cartridges

### **APPLICATION**

Apply the product all over the contact surface.

### **CONSUMPTION**

About 14 m linear cartridge  
100-300 g/m<sup>2</sup> when applied by trowel

### **CLEANING**

Clean the equipment with fresh water or remove mechanically, immediately after use.

### **CONTRAINDICATIONS**

- + Do not use at temperatures below + 3 °C
- + Application is recommended between 10 °C and + 35 °C

### **PACKAGES**

|                  |            |
|------------------|------------|
| Cartridge 280 ml | code 30056 |
| Bucket 6 kg      | code 30093 |
| Bucket 13 kg     | code 30094 |
| Bucket 20 kg     | code 30095 |

### **STORAGE**

The product is guaranteed for 24 months from the date of production.

### **TECHNICAL DATA**

|                          |                                   |
|--------------------------|-----------------------------------|
| base:                    | acrylic                           |
| appearance:              | extra white or colored on request |
| percentage of solid:     | 85%                               |
| customs code:            | 3506 9100                         |
| application temperature: | + 10 °C to +35 °C                 |
| waiting time:            | none                              |
| open time:               | 20 minutes                        |
| setting time:            | 24/36 hours                       |

### **FINAL PROVISIONS**

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com