

TECHNICAL DATA SHEET

REVISED: 13/12/2022

PRIMER SP

PRIMERS AND WALL PREPARATION

PRIMERS AND FLOOR PREPARATION



Acrylic water-based primer for walls and floors, specifically for wet walls with fungi and mold.

Suitable for:

- restoring old walls.
- protecting and preventing fungi and molds on wet walls.
- PRIMER SP prepares the wall surface before applying wall coverings and paints.

Technical features:

- + Exceptional efficiency
- + High yield
- + Low V.O.C. (Volatile Organic Compounds)
- + Penetrates up to 3 cm in the substrate, and creates a consolidation effect

PRODUCT PREPARATION

We recommend to dilute in water at a ratio of 1:1 (1 L of PRIMER SP in 1 L of water). With water base paints, we recommend a dilution of 1:2 (1 L of PRIMER SP in 2 L of water)

APPLICATION

After dilution the PRIMER SP can be immediately applied on wall or floor the surface with a roller or a brush. The product dries in 3/4 hours at 20 – 23°C. The drying time can vary based upon the temperature and characteristics of the work environment.

CONSUMPTION

About 200 gr/m², depending on the porosity of the substrate

CLEANING

We recommend to clean all the work tools with water, immediately after use.

CONTRA-INDICATIONS

Product is not suitable on non-absorbent surfaces (ceramic, glass, laminates). Protect from frost.

PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30172-N	1	litre	Bottle	10
30173-N	5	litres	Tank	4
30174-N	10	litres	Tank	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 13/12/2022

PRIMER SP

PRIMERS AND WALL PREPARATION

PRIMERS AND FLOOR PREPARATION



TECHNICAL PRODUCT DATA

Base	Acrylic Water based
Appearance	White liquid
PH	6.5
Viscosity	500 / 700 cps
Solids percentage	50%
Customs code	3209 1000
Application temperature	+5°C +40°C
Drying Time	3 / 4 hours
Non Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.