

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



VICEVERSA WET SYSTEM is a complete and safe system to applying decorative fiberglass and vinyl wallpaper with any type of backing in wet and/or in direct contact with water (such as showers, saunas, etc.).

PRIMER+ PLUS

Anti-mold, antibacterial and sanitizing PRIMER for walls and floors;

Primer+ Plus contains our exclusive sanitizing gel based on Thymol, THYMOLGEL®.

Thymol, antibacterial and antiviral, is a phenol derived from the Thyme plant.

Suitable for:

- Sanitize new and old walls;
- Protect and prevent the appearance of fungi and mildew;
- Harden and protect the walls surfaces;
- Preparation for the application of paints, wall coverings, vinyl flooring and LVT

TECHNICAL FEATURES

- + Ready-to-use
- + Acrylic Resin basis
- + Does not drip
- + Physical appearance in GEL
- + Very Low V.O.C.
- + Contains Thymol

PRODUCT PREPARATION

Primer+ Plus is a ready-to-use product. The product can also be diluted in water with a ratio of 1:1 (1 liter PRIMER+ PLUS in 1 litres of water).

PRODUCT APPLICATION

Proceed to spread Primer+ Plus on walls and/or floors with a roller or a brush.

The product dries completely in 3/4 hours at 20-23°C. The drying time can vary based upon the temperature and characteristics of the work environment.

CONSUMPTION

About 100-200 gr/m2, depending on the porosity of the substrate

CLEANING

We recommend to clean all the work tools with water, immediately after use.

CONTRA-INDICATIONS

Primer+ Plus is not suitable on non-absorbent surfaces (ceramic, glass, laminates). Protect from frost.

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30196-N	1	Litre	Bottle	10
30193-N	2,5	Litres	Rectangular Bucket	6
30194-N	5	Litres	Rectangular Bucket	4
30195-N	10	Litres	Rectangular Bucket	1

STORAGE

The product is guaranteed for 12 months from the date of production, if stored at temperatures +5 °C to +40 °C.

TECHNICAL PRODUCT DATA

Base	Acrylic, Water Base
Appearance and colour	Light blue gel
PH	7.7
Viscosity	1000-1200 cps
Solids percentage	35%
Customs code	3209 1000
Application temperature	+5°C +40°C
Drying Time	3 / 4 hours
Non-Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



VICEVERSA SPECIAL MS

A modified silylated polymer adhesive created for binding structural components in the building trades, and for wallcoverings and flooring in PVC, LVT, glass fibre wallcoverings in humid environments (bathrooms, saunas etc). Low rate of elasticity.

Suitable for:

- General metalworking
- Items in polyurethane and polystyrene
- Vinyl, and glass fibre wallcoverings
- Flooring in LVT and PVC
- Installation of glass fibre wallcoverings in humid areas (bathrooms, saunas etc)

TECHNICAL FEATURES:

- + Solvent free
- + No water content
- + Low VOC (Volatile Organic Compounds)

GROUND PREPARATION

All grounds should be dry, absorbent (this product also works with non-porous grounds), solid, dust-free and free from paint or oil. Any gaps should be sealed using our two-part epoxy adhesive, EPOXY, and then smoothed.

PREPARATION OF MATERIALS

Before commencing installation, we suggest leaving the materials on site for one day prior to commencing work for acclimatisation to room temperature. Once SPECIAL MS has been applied to the wall, install the product in accordance with the manufacturer's recommended installation temperature.

PREPARATION OF PRODUCT

SPECIAL MS is a ready to use single component adhesive

PRODUCT APPLICATION

SPECIAL MS can be applied directly to the wallcovering using a nr° 1 grooved spatula. Fix the two surfaces together making sure there is contact at all points.

COVERAGE

Coverage depends on the nature of the installation. Approx 250-350g/m².

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PACKAGING

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30191-N (Bianco)	2,5	kg	Rectangular Bucket	1
30110-N (Crystal)	2,5	kg	Rectangular Bucket	1

PRODUCT TECHNICAL DATA

Base	Silylated polymer
Physical appearance	White or clear
Percentage of solids	Approx 75%
Customs code	3909 5090
Operating temperature	+10°C +35°C
Wait time	None
Open time	Approx 30-40 minutes
Complete drying time	48/72 hours

CLEANING

We suggest cleaning using a nitro thinner

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



VICEVERSA PU COAT

VICEVERSA PU COAT (A+B) is a clear opaque coating for the protection and waterproofing of all types of wallcoverings. It makes the wallcovering washable and scratch resistant. It is convenient for both domestic and trade use and can be used in humid environments or where direct water contact may occur (such as in saunas and showers etc)

Suitable for:

- Wallpapers
- Glass fibre wallcoverings
- Non-woven wallcoverings
- Textured vinyl wallcoverings
- Digitally-printed vinyl or non-woven wallcoverings

TECHNICAL FEATURES:

- + Opaque
- + Aesthetically appealing
- + Does not affect the colour of the wallcovering
- + Does not leave marks
- + Does not yellow
- + Solvent free

VICEVERSA PU COAT, in combination with our silylated modified polymer adhesive VICEVERSA SPECIAL MS (white or transparent), makes up a complete and secure system "VICEVERSA WET SYSTEM", for the application of decorative glass fibre wall coverings and any type of vinyl wallcoverings in humid environments and/or in direct contact with water, for example shower, bathroom, sauna etc.

PRODUCT PREPARATION

VICEVERSA PU COAT is a bi-component protective coating, preparing by mixing accurately the two components until a complete homogeneous mixture is obtained.

SURFACE PREPARATION

All surfaces must be dry, absorbent, solid, free from dust, paints and oils. Any gaps should be filled with our ultra-light GLASTER filler. We also recommend using a sealing primer to bind and clean the wall. PRIMER AC is ideal for binding and for cleaning, whereas PRIMER SP is specifically developed to protect and to prevent walls from mould and bacteria where the environment may be humid. To be assured of a complete sanitisation and anti-bacterial protection we recommend using our PRIMER+ PLUS with THYMOLGEL.

APPLICATION

Once VICEVERSA PU COAT is correctly mixed (as described above), apply the product directly on the wallcovering, with a closed cell sponge roller in a single or double layer. Between the first and second layer wait for a min. 4 h at 20-23°C and/or wait upon complete drying. Apply the product within 90 min. after mixing the two components.

ENVIRONMENTAL INSTALLATION CONDITIONS

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



Ambient temperature and of the surface: min +10°C - max. +30°C. Relative air humidity: max. 75%. Also ensure the site has effective air circulation to avoid a build up of humidity in the environment, which could cause hardening problems particularly in close quarters.

COVERAGE

For glass fibre and for textured vinyl: approx 120-150g/m²

For non-woven, paper and vinyl: approx 90-100g/m²

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30203	1	kg	Plastic bottle	1
	200	g	Jar	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Colour	Part A transparent when dry Part B transparent
Base	Two part aliphatic polyurethane
Finish	Opaque (imperceptible to touch)
Physical appearance	Liquid (both A & B)
Viscosity	500-700cps (both A & B)
PH	7.5-8 (both A & B)
Percentage of solids	Approx 36% (total A+B)
Working temperature	Between -10°C to +50 °C
Minimum operating temperature	+5°C
Dust free	30 min. a 20°C
Hardening completed	24 hours

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



VICEVERSA DIAMOND

Adhesive/resin/sealant with a modified silane polymer base, created to bind structural items together. Incorporates hydro-hardening properties.

Suitable for:

- Structural bonding in construction
- Sheet metals, guttering and facias
- Expansion joints between cement materials
- Polyurethane and polystyrene, even outdoors
- Bonding between non-absorbent materials, even outdoors (metals, glass, plastics)
- Strong suction effect

TECHNICAL FEATURES:

- + Solvent free
- + Low elasticity
- + Strong initial grab
- + Low shrinkage
- + Low VOC emissions

SURFACE PREPARATION

All grounds must be dry, absorbent, solid, free from dust, paints and oils. Any gaps should be filled with our ultra-light GLASTER filler.

PRODUCT PREPARATION

Single component adhesive ready to use. Cut the nozzle from the cartridge and use an appropriate sealant gun.

PRODUCT APPLICATION

Apply so that the adhesive contacts every required surface.

COVERAGE

Approximately 15 linear metres per cartridge

CLEANING

We recommend the use of a thinner

GUIDANCE

- Not suitable for use at temperatures below +3°C
- Recommended operating temperature between + 10°C and + 35°C

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 02/11/2022

VICEVERSA WET SYSTEM

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30128B (white)	300	ml	Cartridge	24
30128T (transp.)	300	ml	Cartridge	24

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Base	Modified Silane Polymer
Physical Appearance	Extra white colour or clear
Percentage of solids	Approx 80%
Customs Code	3909 5090
Operating Temperature	+10°C +35°C
Waiting Time	None
Open Time	Approx 30-40 minutes
Total Drying Time	48/72 hours

SAFETY ADVICE

Keep away from babies and small children. Dispose of waste in containers suitable for building materials.

ADVISORY

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.